

Deburring Wheels

Cotton Fiber - Deburring Wheels

- Smooth control and operator feel
- Grind, debur and finish in one step
- Long life vs. standard deburring wheels

S Stainless, high tensile alloys

A Aluminum, non-ferrous metals

DEBURRING WHEELS

Size	Grit	Part No.	Qty Per Box
2 x 1/8 x 1/4	Hard-C	95210	10
2 x 1/8 x 1/4	Med-S	95220	10
3 x 1/8 x 1/4	Hard-C	95300	10
3 x 1/8 x 1/4	Med-S	95330	10



Cotton Fiber - Mounted Points

- A60M - Resin Bond light removal-blending
- A80F - Latex Bond for fine finishing

S Stainless, high tensile alloys

A Aluminum, non-ferrous metals



MOUNTED POINTS

Type	Size		Shank Dia.	Part No.		"0" = 1/2" Max RPM	Qty Per Box
	Dia.	Length		A60M	A80F		
A5	3/4	1-1/8	1/4	96100	97100	45,000	10
B42	1/2	3/4	1/4	96200	97200	61,120	10
B52	3/8	3/4	1/4	96300	97300	81,000	10
B121	1/2	1/2	1/4	---	97400	76,390	10
B122	3/8	3/8	1/4	---	97500	81,370	10
W163	1/4	1/2	1/4	---	97600	33,750	10
W189	1/2	2	1/4	96700	97700	24,000	10
W220	1	1	1/4	---	97800	30,000	10
W222	1	2	1/4	---	97900	20,000	5